

HARRIS FALCON III® RF-335M-STC HANDHELD



TSM-X™ MANET

TrellisWare® technology allows over 200 users to share simultaneous voice, video and Position Location Information

Fast and dynamic net entry in seconds with auto-configuring and self-healing technology



ISR FULL-MOTION VIDEO

Real-time operational picture powered by rugged ISR video receiver expansion module

Proven, leading-edge technology based on TacROVER(e)™ platform and developed with L-3 Communications Systems West



L3 communications
Communication Systems West



DUAL-CHANNEL CRITICAL COMMS

Optimized SWaP handheld with two channels—each capable of voice, data and video

Seamless wideband networking with SATCOM support and MUOS-ready architecture



INTUITIVE BY DESIGN

Mission information at a glance with double-height LCD featuring tabbed multi-channel screen

16-position preset switch and volume are controlled without removing radio from holster

OVERVIEW

Packaged into rugged expansion module; tethering options also available

Local viewing/data crossbanding of encrypted video stream over MANET

BANDS

L, S, C, KU-bands CDL, BE-CDL, DDL, STANAG 7085, VNW

DUAL-CHANNEL PERFORMANCE

R/T 1: LOW BAND

- 30-512 MHz, 5 watt NB or WB
- 10 watt SATCOM
- MUOS support built in
- 10 MHz wide-channel support

R/T 2: HIGH BAND

- 225-450 MHz, 1300-2600 MHz NB or WB
- 10 watt SATCOM
- 40 MHz wide-channel support

CURRENT

- SINGARS ESIP
- HAVEQUICK II
- IW Phase 1/2
- VHF/UHF LOS
- ATC
- P25 Phase 1
- PDA-184
- HPW
- e-BFT
- ASCM

FUTURE

- MUOS
- SATURN
- ANW2®C
- SRW

CURRENT

- TrellisWare TSM-X
- SRW
- ANW2®C
- UHF LOS
- UHF SATCOM

FUTURE

- HAVEQUICK II
- SATURN
- IW Phase 1/2
- P25 Phase 1
- PDA-184
- HPW

HARRIS® TECHNOLOGY TO CONNECT,
INFORM AND PROTECT™

Non-Export Controlled Information

Trademarks and trade names are the property of their respective companies.

© 2017 Harris Corporation 05/17 P5026

harris.com | [#harriscorp](https://twitter.com/harriscorp)